



Tecumseh

SILAJ4492N-FZ

Condensing unit
220 - 240V 1~ 50 Hz

UE 2015/1095, Product Efficiency Report - SEPR

Application : High Temp. Commercial
Refrigerant : R1234yf
Frequency : 50 Hz
Condition: Dew
Operating conditions : EN13215

Evaporating : -10.0 °C
Return gas temp. : 20.0 °C
Superheat : 30 K
Subcooling : 3.0 K

Parameters at full load and ambient temperature 32 °C

rated cooling capacity	P_A	1274	Watt
Rated power input	D_A	732	Watt
Rated COP	COP_A	1.74	Watt/W

Parameters at full load and ambient temperature 25 °C

rated cooling capacity	P_B	1422	Watt
Rated power input	D_B	705	Watt
Rated COP	COP_B	2.02	Watt/W

Parameters at full load and ambient temperature 43 °C

rated cooling capacity	P_3	1032	Watt
Rated power input	D_3	757	Watt
Rated COP	COP_3	1.36	Watt/W

Others items

Capacity control	Fixe
------------------	------

Tecumseh Europe Sales Logistics S.A.S.

2, Avenue Blaise Pascal, 38090 Vaulx Milieu, France - Tel : +33(4) 74 82 24 00

tecsup@tecumseh.com - www.tecumseh.com

Page 1/1

Date 20/01/2021