



Tecumseh

SILAJ4492N-TX

Condensing unit

400V 3~ 50Hz

UE 2015/1095, Product Efficiency Report - SEPR

Application : High Temp. Commercial
Refrigerant : R1234yf
Frequency : 50 Hz
Condition: Dew
Operating conditions : EN13215

Evaporating : -10.0 °C
Return gas temp. : 20.0 °C
Superheat : 30 K
Subcooling : 3.0 K

Parameters at full load and ambient temperature 32 °C

rated cooling capacity	P_A	1273	Watt
Rated power input	D_A	669	Watt
Rated COP	COP_A	1.90	Watt/W

Parameters at full load and ambient temperature 25 °C

rated cooling capacity	P_B	1421	Watt
Rated power input	D_B	649	Watt
Rated COP	COP_B	2.19	Watt/W

Parameters at full load and ambient temperature 43 °C

rated cooling capacity	P_3	1031	Watt
Rated power input	D_3	689	Watt
Rated COP	COP_3	1.50	Watt/W

Others items

Capacity control	Fixe
------------------	------

Tecumseh Europe Sales Logistics S.A.S.

2, Avenue Blaise Pascal, 38090 Vaulx Milieu, France - Tel : +33(4) 74 82 24 00

tecsup@tecumseh.com - www.tecumseh.com

Page 1/1

Date 20/01/2021